



FEATURES

- ▼ Available in sealed beam 1000w Quartz Halogen or 500w incandescent lamp options.
- ▼ Choice of corrosion resistant housings in rugged heavy wall cast marine brass or cast copper free aluminum.
- ▼ Medium flood as standard with narrow, very narrow or wide beam pattern available.
- ▼ High impact protective guard available to prevent damage to lamps and lens.
- ▼ Unique SRV floating lamp assembly provides shock and vibration resistance and extends lamp life.
- ▼ Adjustable mounting allows 360° horizontal rotation, vertical positioning down 45° and up 90°. With handle option vertical up is 60°.
- ▼ Range of colored lens available in red, blue, green and yellow.
- ▼ Includes a watertight connector and 6 feet of 16/3 cord.
- ▼ Field replaceable lens and gasket.
- ▼ 5 year warranty.

APPROVALS

- ▼ UL 1598A - Marine Outside Type Saltwater
- ▼ ABS
- ▼ Conforms to IP 66

APPLICATIONS


- ▼ Marine and wet environments
- ▼ Military ships
- ▼ Drill ships and exploration vessels
- ▼ Tankers
- ▼ Patrol Boats
- ▼ Coast Guard rescue vessels

OPTIONS

To obtain a luminaire with any of the options listed below, please add the following suffix to the part number (not all options can be combined):

- | | |
|--|-----|
| ▼ Guard | GRD |
| ▼ Narrow Spot Light Type | NSP |
| ▼ Very Narrow Spot Light Type (1000w only) | VNS |
| ▼ Wide Floodlight Type | WFL |
| ▼ Handle and Clamp | HDL |
| ▼ Red Colored Lens | RED |
| ▼ Blue Colored Lens | BLU |
| ▼ Green Colored Lens | GRN |
| ▼ Yellow Colored Lens | YEL |

DIMENSIONS



Dimensions in inches



LUMINAIRE TECHNICAL SPECIFICATIONS

HOUSING

Available in heavy wall cast marine brass with a natural finish or a cast copper free aluminum with a white oven-cured polyester powder coat protective finish.

GUARD

Optional stainless steel wire guard available.

OUTLETS

All units are supplied with one sealed watertight cord connector and 25 feet of 16/3 cord.

GASKET

A one-piece high temperature silicone gasket provides a watertight seal between the lens frame and housing. The gasket is field replaceable.

HARDWARE

Stainless steel wing nuts for all types.

VOLTAGE OPERATION

Rated for operation on 120v as standard. Please contact factory for other voltage and frequency options.

LAMP TYPE

A 500w 120v medium floodlight PAR64 incandescent lamp supplied for incandescent units. A 1000w 120v medium floodlight PAR64 quartz halogen lamp is supplied for halogen units, option Q.

LENS

Clear heat resistant glass lens. Optional colored lenses are available in red, blue, green and yellow. The lens is field replaceable.

LAMPHOLDER

Mogul end prong plug-in type lampholders with high temperature leads are supplied as standard.

ORDERING REFERENCES

FLOODLIGHT LUMINAIRES				
DESCRIPTION	MARINE BRASS TYPE	MARINE BRASS WEIGHT (lbs)	ALUMINUM TYPE	ALUMINUM WEIGHT (lbs)
500w Incandescent	749B	60.0	749A	24.0
1000w quartz halogen	749BQ	60.0	749AQ	24.0

SPARE PARTS			
GUARD	INX1060	LENS AND FRAME ASSEMBLY	
LENS	INX2140CLR	Marine Brass units	INX9051B
To order a colored lens replace the CLR with the appropriate suffix below - Red Lens RED Green Lens GRN Blue Lens BLU Yellow Lens YEL		Aluminum units	INX9051A
LAMPS		LAMPHOLDER	
500w MFL 120v	INX3512	Mogul end plug	INX4014
500w NSP 120v	INX3513	LENS GASKET	GKT1146-32.5
500w WFL 120v	INX3634	STANDARD MOUNT	
1000w MFL 120v	INX3514	Marine Brass units	INX7048B
1000w NSP 120v	INX3534	Aluminum units	INX7048A
1000w WFL 120v	INX3649	SWING BOLT/NUT KIT	
1000w VNS 120v	INX3652	Stainless Steel (4 per package)	INX8100