



FEATURES

- ▼ 70 and 100w High Pressure Sodium.
- ▼ Low profile mounting with junction box to the side of the luminaire.
- ▼ Corrosion resistant housing in copper free aluminum.
- ▼ Tool-less entry via four stainless steel over the center cam latches provide a watertight seal and easy access to lamp.
- ▼ Vibration dampening mounting feet.
- ▼ HID luminaires supplied with versatile multi-tapped 120/208/240/277v 60Hz as standard. Also available in 480v 60Hz.
- ▼ Field replaceable globe and gaskets.
- ▼ 5 year warranty

APPROVALS

- ▼ UL 844 – Hazardous Locations
 Class I Divisions 2 Groups A, B, C & D
 Class I Zone 2 Groups IIA, IIB, IIB + H2 and IIC
- ▼ UL 1598A - Marine Outside Type Saltwater
- ▼ Conforms to IP 66

APPLICATIONS


- ▼ Hazardous locations
- ▼ Offshore oil and gas exploration and production
- ▼ Petrochemical
- ▼ Water treatment
- ▼ Pulp and paper processing
- ▼ Corrosive Environments
- ▼ Marine and wet environments
- ▼ Salt and potash mines

OPTIONS

To obtain a luminaire with any of the options listed below, please add the following suffix to the part number (not all options can be combined):

- ▼ 480V 60Hz -486

DIMENSIONS





**HAZARDOUS LOCATIONS CLASS I DIVISION 2 /ZONE 2
HID MOGUL BASE LOW PROFILE LUMINAIRE**

LUMINAIRE TECHNICAL SPECIFICATIONS

HOUSING

Copper free aluminum with an oven cured white polyester powder protective finish with aluminum mounting fittings.

LATCHES

Stainless steel latches.

OUTLETS

All units can be supplied with a wide range of sizes and number of outlets.

GLOBE

High impact, heat resistant, fluted prismatic polycarbonate globe with a retaining stainless steel hook for hands-free lamp replacement.

BALLAST

A multi-tapped ballast offering 120/208/240/277v AC 60Hz versatility is standard. 480v AC 60Hz is available as an option.

LAMP TYPE

Available in mogul base high pressure sodium which operates to -40° F.

GASKET

A one-piece high temperature silicone gasket provides a watertight seal between the lens frame and housing. The gasket is field replaceable.

ORDERING REFERENCES

HID LUMINAIRES	
70w Aluminum Housing with Stainless Steel Mounting Feet	LXACRS10MT
100w Aluminum Housing with Stainless Steel Mounting Feet	LXACRS7MT
70w Aluminum Housing with Aluminum Mounting Feet	LXACRA10MT
100w Aluminum Housing with Aluminum Mounting Feet	LXACRA7MT

SPARE PARTS			
LAMPS		LENS	
70W HPS	INX3662	INX2169	
100W HPS	INX3535	GASKET	
BALLAST		GKT6043-35.5	
70W HPS MULTI-TAP	INX5116	LAMP HOLDERS	
70W 480V 60HZ	INX5234	INX4099	
100W HPS MULTI-TAP	INX5014		
100W 480V 60HZ	INX5056		